

ANPING TAILONG

HARDWARE&WIRE MESH PRODUCTS CO.,LTD

TLWY[®]
TaiLong Fence



SLIDING GATE
**CHAIN LINK FENCE SLIDING GATE/
SUSPENDED GATE**



Mobile:

+86-133-2318-6988
+86-153-6985-6999



Email:

Sales@fence-global.com
Sales@wiremesh-global.com



No.19, Jingsi road,
high-tech-industrialdevelopment
zone, Anping, Hebei, China



Chain Link Fence Sliding Gate/Suspended Gate

Chain-driven sliding doors are made of galvanized material or wire-coated material. To ensure smooth opening and closing, rollers are provided at the top and bottom of the door panel. As a preferred solution for controlling vehicle and pedestrian access, it is widely used in industrial and commercial settings, including factory warehouses, parking lots, administrative areas, residential communities, and villa areas.





DESCRIPTION & CATEGORY

Height: 1.2 m, 1.5 m, 1.8 m, 2.0 m, 2.2 m, 2.5 m, 3.0 m

Width: 4.0 m, 4.8 m, 6.0 m, 10.0 m

Mesh Size: 50 × 50 mm, 60 × 60 mm, 70 × 70 mm

Wire Diameter: 3.0–5.0 mm

Post (round): 48 mm OD, 60 mm OD

Frame Tube: 32 mm OD, 38 mm OD, etc.

Surface Treatment: hot-dip galvanizing;
powder coating;
PVC coating. Includes
doorposts, hinges, nuts,
bolts, and motors.



Features:

- Lightweight and flexible, adjustable opening angle.
- Sufficient strength and durability.
- Equipped with external or internal rollers.
- Corrosion-resistant and rust-proof.
- Widely applicable.
- Long service life.

Suspended Door



Chain Link Fence Suspended Gate



ANPING TAILONG

HARDWARE&WIRE MESH PRODUCTS CO.,LTD

+86-133-2318-6988
+86-153-6985-6999

Sales@fence-global.com
Sales@wiremesh-global.com

No.19, Jingsi road,
high-tech-industrialdevelopment
zone, Anping, Hebei, China

WHATSAPP

